

Fittings / LED Panels**Arial Plus Multi Backlit LED UGR<19 600x600
White Panel - 4000K**

The Arial Plus Multi is our leading wattage switchable panel. The Arial Plus Multi can be installed in areas where TPa rated lighting products are essential, such as emergency exit routes including stairways and corridors.

- High efficiency
- TPa
- Uniform light distribution
- Professional LED Panel
- 0-10V Dimming or DALI Dimming options available

Technical Specification

Product Code	11748
---------------------	-------

Reference

Guarantee	7 Years
EAN	5013588117485
Commodity Code	9405423990
Country of Origin	CN
UNSPSC Code	39111544
Product Application	Commercial / Education / Offices
Product Category	LED Luminaires - Not Plastic

Technical Specification

Watts (W)	20/26/30/36
Volts (V)	220/240
Colour Temp (K)	4000
Lumens (lm)	2983 (20W) / 3851 (26W) / 4390 (30W) / 5159 (36W)
Lumens per Watt (lm/W)	143-149
CRI (ra)	85
Frequency (Hz)	50/60
Energy Consumption (kWh/1000h)	36
Life Hours	50000
Switching Cycles	25000
IP Rating	IP40

Dimensions

Height (mm)	595
Width (mm)	595
Depth (mm)	25

Packaging Information

Height (mm)	595
Width (mm)	595
Depth (mm)	25
Individual Product Weight (kg)	1.7
Single Carton Height (mm)	670
Single Carton Width (mm)	627
Single Carton Depth (mm)	36
Single Carton Weight (kg)	2.2
Individual Volume	0.01512324
Outer Box Qty	4
Outer Carton Barcode	1174800000004
Outer Box Height (mm)	685
Outer Box Width (mm)	640
Outer Box Depth (mm)	250
Outer Box Weight (kg)	13.5
Outer Box Volume	0.1096