

LUIK GEAR TRAY

The Luik range is a tough and robust bulkhead luminaire, constructed from die-cast aluminium with a durable powder coating finish and a polycarbonate diffuser. The light fitting also benefits from an IP65 rating and an IK10 impact rating. Easy to install, available in plain, eyelid and grill bezel, with options of emergency, microwave sensor. The Luik is ideally suited for public buildings, car parks to industrial facilities, in both exterior and interior applications. Available in a choice of finishes.

CREATE YOUR PERFECT LUIK BULKHEAD

1. Firstly choose your style and colour from our plain, eyelid and grill options, which are all available in black, white or grey.
2. Then pick your gear tray, the options are standard, microwave, emergency or microwave emergency.



1: SELECT YOUR CASING STYLE & COLOUR...

CODE	DESCRIPTION	FINISH	COMPLETE PRODUCT LUMEN	DIMENSIONS
61646	Luik plain casing IP65	Textured black	1210	Proj: 64mm Dia: 359mm
61648	Luik eyelid casing IP65	Textured black	770	Proj: 68mm Dia: 359mm
61650	Luik grill casing IP65	Textured black	1010	Proj: 74mm Dia: 359mm
61647	Luik plain casing IP65	Textured grey	1210	Proj: 64mm Dia: 359mm
61649	Luik eyelid casing IP65	Textured grey	770	Proj: 68mm Dia: 359mm
61651	Luik grill casing IP65	Textured grey	1010	Proj: 74mm Dia: 359mm
69231	Luik plain casing IP65	Textured white	1210	Proj: 64mm Dia: 359mm
69232	Luik eyelid casing IP65	Textured white	770	Proj: 68mm Dia: 359mm
69233	Luik grill casing IP65	Textured white	1010	Proj: 74mm Dia: 359mm

Standard, emergency, microwave and microwave emergency gear trays designed to be used with the Luik bulkheads. Create your ideal bulkhead below.



• Die cast aluminium alloy & polycarbonate

2. NOW SELECT YOUR TRAY...

CODE	DESCRIPTION	LAMP	K	DIMENSIONS
61652	Luik gear tray	18W LED module (SMD)	4200	H: 23mm Dia: 282mm
61653	Luik EM gear tray	18W LED module (SMD)	4200	H: 40mm Dia: 283mm
72180	Luik Microwave gear tray	18W LED module (SMD)	4200	H: 32mm Dia: 283mm
72181	Luik Microwave EM gear tray	18W LED module (SMD)	4200	H: 40mm Dia: 283mm