


Comfort EVO Surface



- Economic high performance CCT selectable surface IP44 downlight suitable for commercial and healthcare applications
- Deep cut-off angle for glare control and comfort
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Twist and lock installation bracket design allows quick and easy surface mounting
- Available in black or white finishes
- Polycarbonate housing with unique thermal management for durability and optimum lifespan
- **Please note: Reflector and trim parts (ACOM/TR/*/*) are not required for installation with this kit**
- **Please note: Hawk Emergency Kit cannot be used in conjunction with this downlight**




OCTO
Option Available

Powered by
CASAMBI



Black



Simple twist and lock bracket for easy installation

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP
220/240V	50/60Hz	-20°C to 25°C	L80 60,000	80	3	80°	2	IP44

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	UGR
ACOM1/1/SMF/W	CCT Selectable - White	7W/13W	3000K/4000K	1000lm/1800lm (4000K)	130lm/W (4000K)	23
ACOM1/1/SMF/B	CCT Selectable - Black					
ACOM2/1/SMF/W	CCT Selectable - White	17W/21W		2300lm/2800lm (4000K)		
ACOM2/1/SMF/B	CCT Selectable - Black					

* UGR Value based on (4H - 8H)

CODE (OPTIONS)	DESCRIPTION
/OCTO	OCTO Smart Control

CODE (OPTIONS)	DESCRIPTION
/DD	Digital Dimming (DD1/DD4)

