


Galaxy



- Multi-wattage compact IP65 LED performance downlight suitable for education, commercial and healthcare applications
- Cut-out dimensions suitable to replace most PLC downlights
- Fitting and driver pre-wired with ST18 connectors
- Faceted reflector and optical fresnel lens provides outstanding performance, uniformity and glare control
- Removable twist on, twist off bezel provides option of utilising alternative bezel and drop glass accessories
- Dimmable and Emergency options, standard and Self-Test Emergency available using the Hawk Kit Emergency Pack
- Powered by Philips



OCTO
Option Available

Powered by
CASAMBI



INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP
220/240V	50/60Hz	-20°C to 35°C	L80 36,000	80	5	100°	2	IP65

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	UGR
AGALED	CCT Selectable - Multi-Wattage	11-16W	3000K/4000K	1400-2000lm (4000K)	131-125lm/W (4000K)	24

* UGR Value based on (4H - 8H)

CODE (OPTIONS)	DESCRIPTION
/DM3	DALI Emergency

CODE (OPTIONS)	DESCRIPTION
/OCTO	OCTO Smart Control
/DD	Digital Dimming (DD1/DD3/DD4)

CODE (ACCESSORIES)	DESCRIPTION
AGPL/DG1/W	Drop Glass 1 - Clear outer ring with frosted centre disc c/w Trim Bezel - White
AGPL/DG3/W	Drop Glass 3 - Frosted glass halo with open centre c/w Trim Bezel - White
AHUEMKIT/LI	Maintained/Non-maintained - Universal Emergency Pack

