Guardian

- Ultra-slim profile LED polycarbonate bulkhead
- Supplied with self-adhesive legend
- Self-test as standard
- 20mm side, end and rear cable entries
- LiFePO4 Lithium battery provides improved energy consumption, product reliability and lifetime
- Quick release LED array/gear tray assembly provides the installer the means to faster installation/maintenance
- Viewing distance 18 metres





Open (Anti-Panic) area (0.5 Lux Minimum)**				
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
2.5	3	6.5	3	6.5
4	3	7.5	3	7.5
6	2.5	8	2.5	8



Escape route 2 metres wide (1 Lux minimum) *				
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
2.5	3	7.5	1.8	4.5
4	3	7	1	3.5
-	-	-	-	-

INPUT	HERTZ	TEMP	LIFETIME (HRS)	BEAM ANGLE	CLASS	IP	IK
220/240V	50/60Hz	5°C to 40°C	L70 36,000	130°	2	IP65	IK08

CODE	DESCRIPTION	WATTAGE	CCT	STANDARD MODE	EMERGENCY MODE
AGLED/3M	Daylight - Maintained / Non-Maintained	3W	6500K	173lm	167lm

CODE (ACCESSORIES)	DESCRIPTION
AGLED/KIT	Semi-Recessing Kit
ASBP/30/LI	3.2V 1500mAh LiFePO4 Replacement Battery

FIRE EXIT
KEEP CLEAR