


Helder Circular




315


- All polycarbonate circular bulkhead suitable for external semi-commercial and residential applications
- Fast loop-in / loop-out connections
- CCT selectable between 3000K, 4000K and 6000K
- Body options of black or white with eyelid cover
- Polycarbonate opal diffuser
- Non-dimmable



Min 6 metres
5 seconds to 12 minutes
3 - 10000 LUX



Fitted with
White Eyelid PIR



Fitted with
Black Eyelid

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP
220/240V	50/60Hz	-5°C to 25°C	L80 54,000	80	6	110°	2	IP54

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W
AHELED/CB	Black	12W	3000/4000/6000K	1100lm (4000K)	88lm (4000K)
AHELED/CW	White				
AHELED/CB/PIR	Black - PIR	12.5W	3000/4000/6000K	660lm (4000K)	54lm (4000K)
AHELED/CW/PIR	White - PIR				
AHELED/EB	Eyelid Black	12W	3000/4000/6000K	660lm (4000K)	54lm (4000K)
AHELED/EW	Eyelid White				
AHELED/EB/PIR	Eyelid Black - PIR	12.5W	3000/4000/6000K	660lm (4000K)	54lm (4000K)
AHELED/EW/PIR	Eyelid White - PIR				

