# Pace UGR<19 600x600

- Backlit LED panel suitable for education, commercial and ancillary area applications
- Slimline design allows for installation into shallow ceiling voids
- CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 3 outputs, in one luminaire
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Dimmable and OCTO options available
- TPa as standard
- **Switch Dim, DALI and 0-10V dimming capability using the multi dimmable driver accessories ADDIM/50/MC (see p215 for more information)**
- **Self-Test Panel Pod and Sensor Pod compatible (see p478 - p479 for more information)**




Selectable CCT

UGR<19

Panel Pod™ Emergency

Panel Pod™ Sensor

OCTO Option Available

Powered by CASAMBI

AIRMLED/POD/3NM/ST
Emergency Pod fitted

| INPUT | HERTZ | TEMP | LIFETIME (HRS) | CRI | SDCM | BEAM ANGLE | CLASS | IP |
|---|---|---|---|---|---|---|---|---|
| 220/240V | 50/60Hz | -20°C to 40°C | L80 60,000 | 80 | 6 | 90° | 2 | IP40 |

| CODE | DESCRIPTION | WATTAGE | CCT | LUMENS | LM/W | UGR |
|---|---|---|---|---|---|---|
| **APAC1/60/1** | 600 x 600 CCT Selectable | 20W - 30W | 3000K/4000K/6500K | 2500lm - 3700lm(4000K) | 125lm/W (4000K) | 19 |

| | | |
|---|---|---|
| **AIRMLED/POD/3NM/ST** | Emergency Pod | 5W |
| **APOD/1/3NM/DA** | Emergency Pod DALI | 3W |
| **AIRMLED/POD/MWS** | Sensor Pod | |

* UGR Value based on (4H - 8H)

| CODE (OPTIONS) | DESCRIPTION |
|---|---|
| **/DM3** | DALI Emergency |
| **/OCTO** | OCTO Smart Control |

| CODE (ACCESSORIES) | DESCRIPTION |
|---|---|
| **AARX60K/1** | 600x600 Anti-Ligature Kit |
| **ASRF/60/1** | 600x600 Skylight Recessed Frame |
| **ADDIM/30/MC** | 30W Multi-current Dimmable LED Driver |

| CODE (ACCESSORIES) | DESCRIPTION |
|---|---|
| **APACLED/SK** | Pace Suspension Kit |
| **APRK/60** | 600x600 Plasterboard Recessed Kit |

RECEPTION