


# Mattone



- Universal polycarbonate LED bricklight suitable for residential and hospitality applications
- Plain frame or eyelid option in black and brushed chrome finishes
- Unique adjustable feet allows for installation into multiple brick apertures
- Polycarbonate construction ideal for coastal applications
- Pre-wired with 500mm of rubber insulated cable
- Supplied c/w installation housing for additional protection and ease of installation
- CCT selectable between 3000K and 4000K
- Non-dimmable



Matching Mattone  
Connected by WiZ  
see p59



Brushed Chrome finish



Installed with  
Surface Mounting Box (not  
available in brushed chrome)



Eyelid

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP	IK
220/240V	50/60Hz	-10°C to 40°C	L70 54,000	80	6	100°	2	IP65	IK06

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W
AMATBLED	CCT Selectable - Black				
AMATB/EYE	CCT Selectable - Eyelid - Black				
AMATBLED/BC	CCT Selectable - Brushed Chrome	2W	3000K/4000K	100lm (4000K)	51lm/W (4000K)
AMATB/EYE/BC	CCT Selectable - Eyelid - Brushed Chrome				

CODE (ACCESSORIES)	DESCRIPTION
AMATB/SMB	Surface Mounted Box

