


Primo Three Circuit 1



- Three circuit modern and slimline LED track spot with integral driver suitable for hospitality, residential, retail and ancillary applications
- Lightweight aluminium design provides sleek appearance and easy install
- 350° rotation with 0-90° tilt on the bracket
- Mirror finish anodized reflector
- Anti-glare design to create visual comfort
- Interchangeable 24° and 36° lens accessories ensuring suitability for a range of application installations
- Gold trim ring accessory available for unique appearance
- Triac dimmable as standard, DALI dimmable option also available



Powered by
CASAMBI



Fitted with APRT1/GR/1



White

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP
220/240V	50/60Hz	-20°C to 40°C	L80 36,000	90	3	60 °	1	IP20

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	UGR
APRT1/P3/1/CW/W	Cool White - White	10W	4000K	1000lm	100lm/W	22
APRT1/P3/1/CW/B	Cool White - Black					
APRT1/P3/1/WW/W	Warm White - White	10W	3000K			
APRT1/P3/1/WW/B	Warm White - Black					

CODE (OPTIONS)	DESCRIPTION
/DD	DALI Dimming (/DD3)

CODE (ACCESSORIES)	DESCRIPTION
APRT1/24/1	Interchangeable Lens 24°
APRT1/36/1	Interchangeable Lens 36°

CODE (ACCESSORIES)	DESCRIPTION
APRT/MP/1/W	Monopoint White
APRT/MP/1/B	Monopoint Black
APRT1/GR/1	Gold Ring Attachment

