


Raptor



527

- Compact modern twin spot suitable for industrial and retail applications
- Standard option offers impressive 500 lumen output with high output option giving over 700 lumen outputs, ensuring suitability for a range of applications
- Moulded polycarbonate heads
- Individual adjustable heads allowing ultimate versatility up or down to aim output to desired height
- Self-test as standard with DALI emergency option



Black

INPUT	HERTZ	TEMP	LIFETIME (HRS)	BEAM ANGLE	CLASS	IP	IK
220/240V	50/60Hz	5°C to 40°C	L70 60,000	65°	2	IP66	IK06

CODE	DESCRIPTION	WATTAGE	CCT	EMERGENCY MODE
ARAP/1/W	Non-Maintained - White	3W	6500K	500lm
ARAP/1/B	Non-Maintained - Black			
ARAP/HO/1/W	Non-Maintained - White - HO	5W	6500K	730lm
ARAP/HO/1/B	Non-Maintained - Black - HO			
ARAP/1/W/DA	Non-Maintained - White - DALI	4W	6500K	600lm
ARAP/1/B/DA	Non-Maintained - Black - DALI			

CODE (ACCESSORIES)	DESCRIPTION
ASBP/35	9.6V 1500mAh LiFePO4 Replacement Battery
ASBP/36	3.2V 6600mAh LiFePO4 Replacement Battery
ASBP/37	9.6V 3300mAh LiFePO4 Replacement Battery

