



**ARAZLED/LI/3M/DA/B**



## Features

Slim low profile recessed LED exit sign

LiFePO4 Lithium battery provides improved energy consumption, product reliability and lifetime

DALI emergency as standard

Supplied c/w all legends

If not connected to DALI network self-test mode operates automatically

Viewing distance 24 metres

## General Information

|                                |          |
|--------------------------------|----------|
| Lamp Type                      | LED      |
| Colour / Finish                | Black    |
| Self Test                      | Yes      |
| IP Rating                      | IP20     |
| Class Protection               | 2        |
| Internal / External            | Internal |
| Surface / Recessed / Suspended | Recessed |
| Warranty (Years)               | 6        |
| CE Mark                        | Yes      |
| Length (mm)                    | 366      |
| Width (mm)                     | 96       |
| Height (mm)                    | 223      |
| Accessories                    | ASBP/19  |

## Technical Information

|                  |                   |
|------------------|-------------------|
| Wattage          | 4.5W              |
| Lumens Delivered | 100lm (Emergency) |
| CCT              | 6000K             |
| Input            | 220-240V          |
| Hertz            | 50Hz              |
| Operating Temp   | 5C° to 40C°       |

## Technical Data - ETIM - Emergency luminaire (EC001957)

|                           |                      |
|---------------------------|----------------------|
| Mounting method           | Built-in             |
| Function                  | Escape route signage |
| Monitoring equipment      | Automatic self test  |
| With light source         | Yes                  |
| Colour housing            | Black                |
| Nominal voltage           | 220-240 V            |
| Degree of protection (IP) | IP20                 |
| Protection class          | II                   |
| Max. system power         | 4.5 W                |
| Colour temperature        | 6000-6000 K          |
| Recognition distance      | 24 m                 |
| Width                     | 96 mm                |
| Height/depth              | 223 mm               |
| Length                    | 366 mm               |

Datasheet generated from <https://onetimepim.com> last updated Monday, September 6, 2021 1:25:55 PM