


Freska



- Economic ultra-slim circular LED performance downlight suitable for education, commercial, healthcare and retail applications
- CCT selectable between 3000K, 4000K and 6000K
- Ideal for use in areas with shallow ceiling void
- Edge lit providing excellent uniform illumination
- Triac dimmable as standard
- Standard and Self-Test Emergency available using the Hawk Kit Emergency Pack



INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP
220/240V	50/60Hz	-20°C to 40°C	L80 54,000	80	6	110°	2	IP44

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	UGR	A	B
AFRE1/1	CCT Selectable - 137mm	9W		945lm (4000K)			137mm	116-126mm
AFRE2/1	CCT Selectable - 180mm	12W	3000/4000/6000K	1260lm (4000K)	105lm/W	25	180mm	162-172mm
AFRE3/1	CCT Selectable - 239mm	18W		1890lm (4000K)			239mm	218-228mm

* UGR Value based on (4H - 8H)

CODE (ACCESSORIES)	DESCRIPTION
AHUEMKIT/LI	Maintained/Non-maintained - Universal Emergency Pack
ASBP/12	7.2V 3000mAh Ni-cd Replacement Battery