


Osprey High Rack



- Modern slim profile IP65 LED polycarbonate bulkhead
- Compact high polished reflector design to provide required light level from high mounting heights
- High performance LED's and optical performance allows increased spacing ratios
- Self-test as standard
- Aesthetically designed for modern appearance
- 20mm side and rear cable entries



	Open (Anti-Panic) area (0.5 Lux Minimum) **				
	Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
	10	5.2	14.5	5.2	14.5
	15	5.2	18	5.2	18

	Escape route 2 metres wide (1 Lux minimum) *				
	Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
	2.5	-	-	4.5	20
	4	-	-	2.5	17

INPUT	HERTZ	TEMP	LIFETIME (HRS)	BEAM ANGLE	CLASS	IP	IK
220/240V	50/60Hz	0°C to 40°C	L70 50,000	60°/100°	1	IP65	IK08

CODE	DESCRIPTION	WATTAGE	CCT	STANDARD MODE	EMERGENCY MODE
AOSLED/3M/ST	Maintained / Non-Maintained	8W	6500K	550lm	405lm

CODE (ACCESSORIES)	DESCRIPTION
ASBP/15/LI	6.4V 5500mAh-5 Li-FePO4 Replacement Battery