


Osprey Cold Store



513

- Modern slim profile IP65 LED polycarbonate bulkhead
- Compact high polished reflector design to provide required light level from high mounting heights
- High performance LED's and optical performance allows increased spacing ratios
- Cold store option incorporates an intelligent integral heat management system to operate in cold store applications down to -30°C
- Self-test as standard
- Aesthetically designed for modern appearance
- 20mm side and rear cable entries



	Open (Anti-Panic) area (0.5 Lux Minimum)**				
	Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
	10	5.2	14	5.2	14
	15	5.2	17	5.2	17

	Escape route 2 metres wide (1 Lux minimum) *				
	Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
	10	-	-	4.5	20
	15	-	-	1.6	14.5

INPUT	HERTZ	TEMP	LIFETIME (HRS)	BEAM ANGLE	CLASS	IP	IK
220/240V	50/60Hz	-30°C to 5°C	L70 50,000	60°/100°	1	IP65	IK08

CODE	DESCRIPTION	WATTAGE	CCT	STANDARD MODE	EMERGENCY MODE
AOSLED/3M/CS	Maintained / Non-Maintained - Cold Store	22W	6500K	445lm	354lm

CODE (ACCESSORIES)	DESCRIPTION
ASBP/16	4.8V 4Ah Ni-Cd Replacement Battery (for use with Cold Store fitting)

