


Gamma and Gamma Mini




- Ultra slim modern polycarbonate wall/ceiling light suitable for education and residential applications and ancillary areas
- Matt white finish to body and diffuser with optional chrome trim ring
- CCT selectable between 3000K and 4000K
- Rear fixing bracket and terminal housing for ease of installation
- Microwave sensor set to 15 minutes at 3 metres (non-adjustable)
- /MWS and /MWS/M3 versions operate as "Primary" and can be used in conjunction with standard "Secondary"
- /MWS and MWS/M3 has integral photocell isolation switch
- Non-dimmable



Connected by
WIZ

Matching
OCTO Gamma and Gamma
Mini Connected by WIZ
see p46 and p47



Fitted with
Chrome Trim Bezel

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP	IK
220/240V	50/60Hz	-5°C to 35°C	L70 54,000	80	6	110°	2	IP54	IK09

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	A	B
AGAMLED/CCT	CCT Selectable	17W	3000/4000K	1800lm (4000K)	106lm (4000K)	296mm	53mm
AMGAMLED/CCT		10W		1200lm (4000K)	115lm (4000K)	250mm	50mm

CODE (OPTIONS)	DESCRIPTION
/M3	Emergency
/MWS	Integral Microwave Sensor

CODE (ACCESSORIES)	DESCRIPTION
AGAMLEDBZ/CH	Gamma Chrome Trim Ring
AMGAMLEDBZ/CH	Gamma Mini Chrome Trim Ring
ASBP/24	4.8V 2Ah Ni-cd Replacement Battery