



DATASHEET



BATMCW5

230V 5ft 41W Modular CCT and Wattage Adjustable Batten

www.mlaccessories.co.uk



MLA PART CODE	BATMCW5
DESCRIPTION	230V 5ft 41W Modular CCT and Wattage Adjustable Batten
NET WEIGHT (KG)	1.6
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1525 Width - 61 Projection - 70
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
IK RATING	IK08
WATTAGE (W)	22/28/34/41
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	3300/3400/3400,4000/4300/4200,4700/5100/4900,5400/6000/5600
LUMENS LIGHT SOURCE ONLY (LM)	3500/3800/3600,4500/4900/4700,5200/5800/5400,6200/6900/6400
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	173/174/169/167
CIRCUIT WATTAGE (W)	22.1/28.4/34.2/41.2
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.10/0.13/0.15/0.18
SVM	0.01
PST-LM	0.02
BEAM ANGLE (DEGREES)	120
L70B50 LIFESPAN (HRS)	100000

DIMMABLE	No
EMERGENCY CONVERSION KIT	MODEMKIT
OPERATING TEMPERATURE	-20~45°C
INPUT VOLTAGE	230V 50Hz
CABLE GLAND INCLUDED	No
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 40W OUTPUT VOLTAGE - 50-133V OUTPUT CURRENT - 200/250/300/350mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 90 CASE TEMPERATURE (Tc) - 80°C
WARRANTY	7year(s)
MANUFACTURED IN ACCORDANCE WITH	BS 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5061061272855

Date Created: 10/02/2026 15:22

