SAVE ENERGY, MONEY & TIME

RACK BAY

Quick and easy installation
Suitable to mount between 3 – 14m high
Colour switchable between 3000K and 4000K
Wattage switchable from 60W to 240W
Sensor and mmergency bolt on



t +44 (0) 16 04 49 51 51
e sales@collingwoodgroup.com
collingwoodlighting.com

By INOVARA

COLLINGWOOD
LIGHTING

COLLINGWOOD
LIGHTING

WATTAGE SWITCHABLE

Rack bay provides both the output of a single wattage or three wattages within the same product. Adjust the wattage switch during installation.

Product	0-10V output	Product	DALI-2 output
LBR1V	60-80-100W	**LBR1D**	100W
LBR2V	160-180-200W	**LBR2D**	200W
LBR3V	200-220-240W	**LBR3D**	240W

LIGHT QUALITY (CCT SWITCHABLE)

Choose the ideal CCT for the environment you are using your Rackbay. 2 colour temperatures which can be switched during installation.

3000K Warm White



4000K Cool White



PIR

Ideal for use in aisles to avoid nuisance triggering.



MICROWAVE

Ideal for automated zones to sync electric and natural light.



EMERGENCY BOLT-ON

Ideal for aisles, corridors and open areas.



QUICK & EASY INSTALL

Tool-less, plug-in and twist sensors make installation quick & easy. Even interchange your sensors should your floorspace be re-configured.

PRODUCT FEATURES

CCT | W | IP20 | IK07 | 150lm/W | A G D | 5 Year Warranty

PRODUCT CODES

Code	Wattage/lumen	Dimming
LBR1V	60-80-100W - 8700-15000lm	0-10V
LBR2V	160-180-200W - 22400-30000lm	0-10V
LBR3V	200-220-240W - 28000-36000lm	0-10V
LBR1D	100W - 14500-15000lm	DALI-2
LBR2D	200W - 28000-30000lm	DALI-2
LBR3D	240W - 33600-36000lm	DALI-2

Code	Accessories
HBDLS	Daylight harvesting sensor with photocell
HBPIRDLD	Motion sensor - daylight dimming/harvesting
HBMWS	Microwave sensor - daylight threshold switch
HBREM	Remote control for commissioning
EMBOLTMRACK	Manual-test racking emergency bolt-on
EMBOLTSRACK	Self-test racking emergency bolt-on
LB2XBRKT	2 x Mounting brackets