

DATASHEET



HEX6

HELIX ONE 6FT 230V IP66 IK10 31W Modular Non-Corrosive Fitting - 4000K

www.mlaccessories.co.uk

MLA PART CODE	HEX6
DESCRIPTION	HELIX ONE 6FT 230V IP66 IK10 31W Modular Non-Corrosive Fitting - 4000K
NET WEIGHT (KG)	2.35
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1865 Height - 81 Width - 95 Projection - 81
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP66
IK RATING	IK10
WATTAGE (W)	31
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	4515
LUMENS LIGHT SOURCE ONLY (LM)	5255
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	165
CIRCUIT WATTAGE (W)	31.71
CCT	4000K
LIGHT COLOUR	Cool White
CRI	≥80
SDCM	<6
RUNNING CURRENT (A)	0.145
SVM	0.075
PST-LM	0.104
BEAM ANGLE (DEGREES)	120
L70B50 LIFESPAN (HRS)	70,000

LED COMPATIBLE	Yes
DIMMABLE	No
EMERGENCY CONVERSION KIT	MODEMKIT2
OPERATING TEMPERATURE	-20~45°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270892260

Date Created: 07/10/2026 09:58

