

DATASHEET



HEXSCW5

HELIX SHIFT 5FT 230V IP66 IK10 Quad Wattage Modular Non-Corrosive Fitting - CCT Adjustable

www.mlaccessories.co.uk

MLA PART CODE	HEXSCW5
DESCRIPTION	HELIX SHIFT 5FT 230V IP66 IK10 Quad Wattage Modular Non-Corrosive Fitting - CCT Adjustable
NET WEIGHT (KG)	1.85
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1565 Height - 81 Width - 95 Projection - 81
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP66
IK RATING	IK10
WATTAGE (W)	28/34/41/49
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	3955/4345/4095/4795/5300/4970/5705/6305/5920/6660/7400/6925
LUMENS LIGHT SOURCE ONLY (LM)	8340
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	168
CIRCUIT WATTAGE (W)	49.3
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	≥80
SDCM	<6
RUNNING CURRENT (A)	0.221
SVM	0.038
PST-LM	0.128
BEAM ANGLE (DEGREES)	120
L70B50 LIFESPAN (HRS)	70,000

LED COMPATIBLE	Yes
DIMMABLE	No
EMERGENCY CONVERSION KIT	MODEMKIT2
OPERATING TEMPERATURE	-20~45°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
WARRANTY	7year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270892703

Date Created: 07/10/2026 10:14

