

MIMAS MINI LED TILT DOWNLIGHT

RESIDENTIAL

FEATURES & BENEFITS

- 2 year Warranty
- 3W LED 3000K or 4000K
- 3000K - 136 Lumens (White)
4000K - 136 Lumens (White)
3000K - 107 Lumens (Black)
4000K - 116 Lumens (Black)
3000K - 128 Lumens (Stainless Steel)
4000K - 144 Lumens (Stainless Steel)
- 51° beam angle | L70 - 30,000 hours
- Ideal for lighting bathrooms, coves, canopies and feature lighting
- Requires 24V constant voltage driver
- Must be wired in parallel | 9° tilt
- Can be dimmable with KSRDL292-93, dimmer list available on website

COLOUR OPTIONS

Black, Stainless Steel, White

CONSTRUCTION

Body - Cast Aluminium
Bezel - Cast Aluminium or AISI 304L
Stainless Steel

CLASSIFICATIONS



DIMENSIONS

KSRDL466-71
Diameter: 50mm
Height: 36mm
44mm
Cable: 850mm



SCAN QR CODE
FOR DATA SHEETS



KSRDL466



KSRDL468



KSRDL470

CODE

DESCRIPTION

KSRDL466	Mimas Mini 3W 3000K LED Tilt Downlight - White**
KSRDL467	Mimas Mini 3W 4000K LED Tilt Downlight - White**
KSRDL468	Mimas Mini 3W 3000K LED Tilt Downlight - Black**
KSRDL469	Mimas Mini 3W 4000K LED Tilt Downlight - Black**
KSRDL470	Mimas Mini 3W 3000K LED Tilt Downlight - Stainless Steel**
KSRDL471	Mimas Mini 3W 4000K LED Tilt Downlight - Stainless Steel**
KSRDL274	4W Mini 24V Constant Voltage IP65 LED Driver (1 driver per fitting)
KSRDL287	20W 24V Constant Voltage IP67 LED Driver* (up to 5 fittings)
KSRDL288	60W 24V Constant Voltage IP67 LED Driver* (up to 15 fittings)
KSRDL292	25W 24V Constant Voltage IP20 Dimmable Driver* (up to 8 fittings)
KSRDL293	50W 24V Constant Voltage IP20 Dimmable Driver* (8-12 fittings)