

FIREBREAK QR SELECT DUAL PRO

The Firebreak Qr Select Dual Pro downlight is one of the latest luminaires in our Qr Select range. Not only does it have all the functionality of the standard Firebreak Qr Select Dual product, the Pro version comes with a lever connector to speed up and make it easier to install.

Whether you want a choice of dual wattages or a different CCT colour, this is the ideal product for you. It has been designed as a cost effective one-piece downlight, suitable for all domestic applications where you are unsure what the customer requires. This will save you time and money on site visits.

Firebreak Qr Select Dual Pro incorporates switches on top of the fitting, which allow the end user to choose which colour temperature they want to use (2700K, 3000K, 4000K or 6000K) and whether they want a 5W or 7W output.

DUAL PRO	5W	7W	CRI:Ra
2700K	560 Lumens	700 Lumens	82
3000K	590 Lumens	760 Lumens	82
4000K	640 Lumens	820 Lumens	82
6000K	635 Lumens	795 Lumens	82

**PRO LEVER CONNECTOR
INCLUDED, AS STANDARD**



**SWITCHABLE COLOUR
TEMPERATURE & WATTAGE**



**IP65 RATED,
AS STANDARD**



FIREBREAK QR SELECT DUAL PRO

DOWNLIGHTS



CODE

DESCRIPTION

KSRFRD386	Firebreak Qr Select Quad CCT Dual-Wattage Dimmable Pro LED Downlight
-----------	--

FEATURES & BENEFITS

- 5 year Warranty
- Quad CCT dual-Wattage LED (5W/7W)
- Set the output of the fitting to 5W or 7W via the drive current selector switch
- Switch between 2.7K, 3K, 4K & 6K
- New Pro lever connector makes installation quicker and easier
- Up to 820 Lm | L70 - 54,000 hours
- CRI:Ra>84 | Dimmable | 64° Beam
- Up to 128 Lumens per circuit Watt
- Phase dimmable as standard - Please see website for recommended dimmers: www.ksrlighting.com

COLOUR OPTIONS

White (Supplied)

(Please see pages 44-45 for colour bezel options)

CONSTRUCTION

Body - Cast Aluminium
Bezel - Polycarbonate

CLASSIFICATIONS

IP65



DIMENSIONS

Diameter: 85mm
Height: 54mm

72mm



SCAN QR CODE
FOR DATA SHEETS