

# ROMA SELECT

## RESIDENTIAL RANGE

The Roma Select bulkhead revolutionises the installation process with its adaptable 'one size fits all' design in 3 different body sizes. The range offers a selection of colour temperatures and power outputs, all housed within the same structure. This flexibility allows both installers and users to tailor their lighting according to specific needs without being constrained by a fixed configuration.

Constructed from polycarbonate for both the body and diffuser, the bulkhead is designed for durability, achieving an IK10 toughness rating and IP65 ingress protection. This ensures a reliable interior lighting solution that caters to a variety of requirements.

The newly introduced XL version, with its 400mm diameter and selectable output ranging from 15W to 24W, is equipped with 5CCT technology, offering a spectrum of colour temperatures from 2700K to 6000K. This makes it an excellent choice for both commercial and residential settings that demand a large high output luminaire.

The large variant, featuring a 315mm diameter body, is also versatile for both commercial and residential use, providing switchable 3CCT and power outputs from 10W to 20W.

For smaller spaces such as domestic utility rooms and sanitary areas, the 250mm model is ideal. It offers switchable colour temperatures (3000K, 4000K, and 6000K) and outputs of 8W or 12W, with emergency versions a new addition for this range.

Employing custom-engineered, high-efficiency LED chips with a lifespan of L70 - 40,000 hours, the bulkhead delivers an outstanding efficiency of up to 122 Lumens per circuit watt. This performance is supported by a 5-year warranty.

Completing the range are versions with integral on/off Microwave, Emergency, and Microwave with Corridor Function, along with XL and Mini versions, reinforcing the Roma Select bulkhead's status as the definitive solution for interior lighting needs.



SCAN QR CODE FOR LUMEN DATA



# ROMA SELECT BULKHEAD

RESIDENTIAL



## CODE DESCRIPTION

KRSRF400	Roma Select Multi-Wattage 3CCT Surface Fitting
KRSRF401	Roma Select Multi-Wattage 3CCT Surface Fitting with Integral Emergency
KRSRF402	Roma Select Multi-Wattage 3CCT Surface Fitting with Microwave Sensor
KRSRF403	Roma Select Multi-Wattage 3CCT Surface Fitting with Microwave Sensor & Integral EM
KRSRF404	Roma Select Multi-Wattage 3CCT Surface Fitting with Corridor Function
KRSRF405	Roma Select Multi-Wattage 3CCT Surface Fitting with Corridor Function & Emergency
KRSRF411	Roma Select Chrome Rim with Opal Diffuser

## FEATURES & BENEFITS

- 5 year Warranty
- Colour Temperature & Wattage selectable 3000K, 4000K or 6000K LED and 10W, 14W & 20W outputs
- Up to 119 Lumens per circuit Watt
- Wall or ceiling mountable
- L70 - 40,000hrs
- CRI: Ra>84
- Emergency, Microwave & Corridor Function options available
- Self test emergency available to order
- Suitable for Besa Box mounting

## COLOUR OPTIONS

White  
(Optional Chrome rim available)

## CONSTRUCTION

Body & Diffuser - Polycarbonate  
Rim - ABS

## CLASSIFICATIONS



## DIMENSIONS

KRSRF400-05  
Diameter: 315mm  
Depth: 82mm



SCAN QR CODE  
FOR DATA SHEETS