

SpektroLED®EVO



SPEKTROLED® EVO SMART DOWNLIGHT

- 230V direct to fixture with loop in-loop out first and second fix connectors
- RGB and CCT adjustable via SmartKnight app
- CCT adjustable 3000K - 6000K
- Wi-Fi Connectivity IEEE 802.11 b/g/n (2.4Ghz only)
- Complete with white bezel as standard
- Additional 5 colourways of interchangeable bezels available (Matt Black, Polished Chrome, Brushed Chrome, Brushed Brass and Antique Brass)
- Complies with the latest energy efficiency standards
- Fire-rated - 30/60/90min solid timber, 30min web joist and 30min i-joist (staircraft)
- IC rated (insulation contact)*
- Acoustic rated ISO 10140-2:2010
- Dimmable**

Construction: Pressed steel

Driver: Integral

Lamp type: SMD LED

Beam angle: 60°



Code	Max. Wattage	Colour	CCT	Lumens	Cut-out (mm)	Dimensions (mm)	Min. Void (mm)	Recessed Depth
SPKEVFKRGBW	8W	3000-6000K	3000-6000K	Up to 855lm	Ø: 70	Ø: 90 P: 6	43	43

* With mineral wool style insulation only, please see page 215 and product instructions for more information

** Dimmable via App only

