



DATASHEET



WPASCWA

230V IP65 IK10 4 x Wattages and 3 x CCT
Asymmetric Wall Pack with Photocell Sensor

www.mlaccessories.co.uk



MLA PART CODE	WPASCWA
DESCRIPTION	230V IP65 IK10 4 x Wattages and 3 x CCT Asymmetric Wall Pack with Photocell Sensor
NET WEIGHT (KG)	1.1
FINISH	Black
DIFFUSER	Clear
DIMENSIONS (MM)	Height - 217 Width - 309 Projection - 162
CONSTRUCTION	Construction - Polycarbonate
IP RATING	IP65
IK RATING	IK10
WATTAGE (W)	14/17/21/24
MAX. WATTAGE (W)	24
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1755/2110/2545/2830/1865/2230/2710/3095/1800/2170/2600/2955
LUMENS LIGHT SOURCE ONLY (LM)	1990/2410/2910/3320/2145/2595/3125/3565/2045/2490/3015/3445
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	143
CIRCUIT WATTAGE (W)	24.06
CCT	3000/4000/6000K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.1120
DISPLACEMENT FACTOR	>0.7
SVM	0.006
PST-LM	0.026
BEAM ANGLE (DEGREES)	150

L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes
DIMMABLE	No
OPERATING TEMPERATURE	-20~45°C
INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 39.9W OUTPUT VOLTAGE - 54-114V OUTPUT CURRENT - 350mA POWER FACTOR - 0.80-0.95 EFFICIENCY FULL LOAD - 92.5 ISOLATION - I/P-FG:100MΩ/500Vdc/25 /70% RH AMBIENT TEMPERATURE (Ta) - -20 ~ 50°C CASE TEMPERATURE (Tc) - 85°C
SENSOR TYPE	Photocell
SENSOR OVERRIDE	Yes
SENSOR LUX SETTINGS	On: 10-25lux, Off: 40-55lux
STANDBY POWER	0.3W
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5061061276419

Date Created: 10/02/2026 15:40

