



XVR111C\_noir

**EV-Charging Station 22kW 3ph attached cable with CT 1ph one MONTA**

**Technical Features**

**Power**

|                          |           |
|--------------------------|-----------|
| Power per charging point | 22 kW     |
| Connected load           | 0.1-22 kW |

**Frequency**

|           |            |
|-----------|------------|
| Frequency | 50 - 60 Hz |
|-----------|------------|

**Power supply**

|                                   |   |
|-----------------------------------|---|
| Number of phases for power supply | 3 |
|-----------------------------------|---|

**Electric current**

|                  |      |
|------------------|------|
| Rated current IN | 32 A |
|------------------|------|

**Connectivity**

|                           |   |
|---------------------------|---|
| Number of charging points | 1 |
|---------------------------|---|

**Functions**

|                      |     |
|----------------------|-----|
| With load management | Yes |
|----------------------|-----|

**Equipment**

|                                         |     |
|-----------------------------------------|-----|
| Number of house sockets                 | 0   |
| With circuit breaker                    | No  |
| With emergency release at power failure | Yes |

**Connection**

|                     |         |
|---------------------|---------|
| Connector/plug type | Type 2S |
|---------------------|---------|

**Dimensions**

|            |              |
|------------|--------------|
| Dimensions | 370 x 250 mm |
| Height     | 370 mm       |
| Width      | 250 mm       |
| Depth      | 150 mm       |

**Installation, mounting**

|             |               |
|-------------|---------------|
| Mounting on | Wall mounting |
|-------------|---------------|

**Safety**

|                               |      |
|-------------------------------|------|
| Ingress Protection (IP) class | IP55 |
| Impact resistance IK          | IK10 |

**Use conditions**

|                       |             |
|-----------------------|-------------|
| Operating temperature | -25 - 50 °C |
|-----------------------|-------------|

**Voltage**

|                 |           |
|-----------------|-----------|
| Nominal voltage | 380-415 V |
|-----------------|-----------|

**Materials**

|          |         |
|----------|---------|
| Material | Plastic |
|----------|---------|

**Illustrations | Drawings**

